

DV18DEW2Z

Cordless Impact Driver Drill 18V

4966376404780



High torque and working speed

Very short and easy handling

Reactive Force Control





Batteries not included

Specifications		
Voltage		18V
Max. capacity drilling	Wood	52 mm
	Steel	13 mm
	Brick	13 mm
Max. torque	Hard joint	70 Nm
	Soft joint	40 Nm
No-load speed	Low mode	0 - 550 /min.
	High mode	0 - 2,000 /min.
Slip torque	Stages	22
	Torque	1.0 - 4.5 Nm
No-load impact rate	High mode	0 - 30,000 /min.
Motor type		Brushless
Overall length		159 mm
Weight with BSL1850MA ¹		1.9 kg

Characteristics

High torque and high working speed to quickly perform tough applications

Very short for optimum manoeuvrability and easy handling Reactive Force Control (RFC) stops the motor when the tool bit is

suddenly overburdened to reduce twisting of the main unit and prevents potential injury

Constant speed control provides additional power so that the motor can maintain its speed under load

Ergonomic soft grip handle for optimal control and longer comfortable working

22 torque settings for best adjustability

Brushless motor for high power, less wear and a long service life

Scope of delivery

DV18DEW2Z: Stackable case HSC II

¹ Weight according to EPTA-2004 procedure.

² Standard accessories vary by country or area.

Read everything about our services at **hikoki-powertools.com**

