



Specifications	
DV18DC	
Battery Voltage	18V
Drill chuck	1.5 - 13mm keyless
Max. Brick	20mm
Max. Metal	16mm
Max. Soft Wood	102mm
No load speed	0-500/min / 0-2000/min
Max. Torque (Hard/Soft)	140Nm / 70Nm
Dimensions (L x H x W)	190 x 267 x 70mm
Weight	2.8kg with BSL36A18
WH18DC	
Battery Voltage	18V
Max. Bolt	5-18mm
Max. HT Bolt	5-14mm
Max. Self Drilling screw	Ø3-5.6mm
Tighting Torque	210Nm (Power Mode)
No load speed	0-3400/min (Power Mode)
	0-900/min (Soft Mode)
Full load impact rate	0-4000/min (Power Mode)
	0-1900/min (Soft Mode)
Dimensions (L x H x W)	114 x 241mm
Weight	1.6kg with BSL36A18

## Characteristics DV18DC

Industry's top class power and drilling speed for toughest applications
Improved airflow design and heat sink keep electronics cool
Robust aluminium gear housing provides additional rigidity
RFC technology and a Gyro sensor detect overburdening of the tool bit
and stop the motor to reduce twisting of the main unit
Compact body to work in tight and hard to reach spaces

## **Characteristics WH18DC**

Compact and lightweight: only 114 mm short and 1.6 kg light allows working in narrow spaces with ease all day long Powerful and fast: 210 Nm tightening torque for hardest jobs Sensitive trigger starts fastening operation at 100 rpm so delicate screws don't get overtightened
Three bright LEDs for thorough illumination
IP56 rating due to coated electronics for full weather protection and against dust

## Standard accessories<sup>3</sup>

Charger UC18YSL3 2 x BSL36A18 batteries HSC3 stackable case

Read everything about our services at **www.hikoki-powertools.co.uk** 

